


5 way lever push wire connector Biz'Wing mini 2.5 0.2-2.5 mm² (x 50)

Mini size for optimising your installations!



Caracteristics

Number of inputs : **5**

Length (mm) : **24.5**

Width (mm) : **16.3**

Height (mm) : **8.5**

Norms

EN 50581:2012 ; EN
 ☑ 60998-1:2004 ; EN
 60998-2-2:2004

Benefits

- It is important to strip the wires up to 11 mm.
- Tiny size: save space and optimize your installations.
- Flexible and ergonomic levers provide for simple utilization.
- For flexible and rigid wires.
- Transparent casing makes it easy to check the connections.

Compliance marks



GENERAL INFORMATION

Technical details

Section for inserting flexible and rigid wires: 0.2 to 2.5 mm².

Glow wire resistance: 850 °C.

Max. ambient operating temperature: 85 °C.

Voltage (V): 450.

Intensity (A): 24.

Strip off 11 mm.

Test point.

Material: polycarbonate.

Instructions

1. Strip wires precisely up to 11 mm.
2. Do not twist multi-strand wires.
3. Open the levers.
4. Insert the stripped wires into the bottom of the connector.
5. Close the levers.



LOGISTIC INFORMATION

 Packaging**Carton box**

Height (cm) : 4,3

Length (cm) : 10

Depth (cm) : 8,6

Net weight (kg) : 0,15

Gross weight (kg) : 0,185

 Outer package 1

x 60.00

Carton box

Height (cm) : 28,4

Length (cm) : 45

Depth (cm) : 23

Net weight (kg) : 10,83

Gross weight (kg) : 11,4

 Outer package 2

x 1800.00

Pallet

Height (cm) : 120

Length (cm) : 80

Depth (cm) : 130

Net weight (kg) : 342

Gross weight (kg) : 357

