

Bi-metal CLIC II hole saw Ø 57 mm



Characteristics

Ø (mm) : **57**
 Depth of cut (mm) : **44**
 Steel (tr/min) : **170-110**
 Stainless steel (tr/min) : **85-55**
 Recommended speed in wood and PVC (tr/min) : **2000-1500**

Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

GENERAL INFORMATION

Description

Supplied without arbor or pilot drill.

Technical details

Material: HSS steel with 8% cobalt.
 Teeth per inch: 4/6.

Advice

Do not use with hammer mode.

Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm

LOGISTIC INFORMATION

Packaging



Blister package

Height (cm) : 16,6
 Length (cm) : 8,6
 Depth (cm) : 5,8
 Net weight (kg) : 0,185
 Gross weight (kg) : 0,211



3 700420 341673

Outer package 1



x 6

Carton box

Height (cm) : 18
 Length (cm) : 20,7
 Depth (cm) : 13,2
 Net weight (kg) : 1,266
 Gross weight (kg) : 1,351



3 700420 339939

Outer package 2



x 72

Carton box

Height (cm) : 40
 Length (cm) : 60
 Depth (cm) : 40
 Net weight (kg) : 13,32
 Gross weight (kg) : 15,692



3 700420 342212

Outer package 3



x 864

Pallet

Height (cm) : 135
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 159,84
 Gross weight (kg) : 198,304



3 700420 345060