

Terminal blocks 6 mm² 41A black polypropylene (x 10)



Characteristics

Colour : **Black**
 Section (mm²) : **6**
 Current (A) : **41**
 Voltage (V) : **400**
 Length (mm) : **109**
 Height (mm) : **14**
 Depth (mm) : **17**
 Quantity : **10**

Norms

- ✓ EN 60998-2-1, NF
- ✓ EN 60695-2
- ✓ IP 20

Benefits

- Ultra-flexible blocks.
- Can be separated in 1.5 turns without the use of tools.

Compliance marks



ENVIRONMENTAL PROFILE



¹ Net volume of freshwater consumed - ² Total primary energy use during the life cycle - ³ Abiotic resource depletion - elements

* Data verified and published on PEP ecopassport

GENERAL INFORMATION

Description

12-way polypropylene connector strips.
Supplied with screws engaged at 1/3.

Technical details

Glow wire test: 960 °C.

LOGISTIC INFORMATION

Packaging



Plastic film

Height (cm) : 11
 Length (cm) : 9
 Depth (cm) : 3
 Net weight (kg) : 0,297
 Gross weight (kg) : 0,307



Outer package 1



Carton box

Height (cm) : 44
 Length (cm) : 16
 Depth (cm) : 13
 Net weight (kg) : 7,425
 Gross weight (kg) : 7,68

