

Terminal blocks 25 mm<sup>2</sup> 101A black polypropylene (x 10)

## Characteristics

Colour : **Black**  
 Section (mm<sup>2</sup>) : **25**  
 Current (A) : **101**  
 Voltage (V) : **400**  
 Length (mm) : **204**  
 Height (mm) : **24**  
 Depth (mm) : **32**  
 Quantity : **10**

## Norms

- ✓ EN 60998-2-1, NF
- ✓ EN 60695-2
- ✓ IP 20

## Benefits

- Ultra-flexible blocks.
- Can be separated in 1.5 turns without the use of tools.

## Compliance marks



## ENVIRONMENTAL PROFILE



<sup>1</sup> Net volume of freshwater consumed - <sup>2</sup> Total primary energy use during the life cycle - <sup>3</sup> Abiotic resource depletion - elements

\* Data verified and published on PEP ecopassport

## GENERAL INFORMATION

## Description

12-way polypropylene connector strips.  
Supplied with screws engaged at 1/3.

## Technical details

Glow wire test: 960 °C.

## LOGISTIC INFORMATION

## Packaging



## Plastic film

Height (cm) : 23  
 Length (cm) : 5  
 Depth (cm) : 15  
 Net weight (kg) : 1,226  
 Gross weight (kg) : 1,254



## Outer package 1



## Carton box

Height (cm) : 26  
 Length (cm) : 23  
 Depth (cm) : 18  
 Net weight (kg) : 6,13  
 Gross weight (kg) : 6,27

