

Wire pulling lubricant BIZ'LUB



Benefits

- Non-flammable, non-corrosive, non-toxic.
- For use with high and low-current cables.
- High lubricating capability.

GENERAL INFORMATION

Technical details

Ph neutral (6.5 ± 0.5).
 Operating temperature: -5°C to $+82^{\circ}\text{C}$ (freezes at -5°C).
 Storage temperature: $+4^{\circ}\text{C}$ to $+40^{\circ}\text{C}$.
 Density: 1.010 ± 0.01 g/ml.
 Viscosity: 3400 ± 200 cps.
 Dry residue: 12°C .
 Volume: 1 l.

Life span

5 years.

Application(s)

To ease passage of cables and wires through electrical conduits, ducts and pipes.

Instructions

1. Leave to dry before switching on power.

LOGISTIC INFORMATION

Packaging



Plastic bottle

Height (cm) : 29
 Length (cm) : 8
 Depth (cm) : 8
 Net weight (kg) : 1,03
 Gross weight (kg) : 1,08



3 701395 139432

Outer package 1



Carton box

Height (cm) : 31
 Length (cm) : 34,5
 Depth (cm) : 26,5
 Net weight (kg) : 12,36
 Gross weight (kg) : 13,41



3 701395 139456

x 12.00

Outer package 2



Pallet

Height (cm) : 110
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 333,72
 Gross weight (kg) : 377,07



3 701395 139470

x 324.00