

Double-sided PE foam tape white 19 mm x 10 m x 0.95 mm



Characteristics

Colour : **White**
 Length (m) : **10**
 Width (mm) : **19**
 Thickness (mm) : **0.95**

Benefits

- Suitable for indoor and outdoor use (high resistance to UV, humidity and solvents).
- Excellent performance against shearing.
- Can be torn by hand.

GENERAL INFORMATION

Description

Double-sided PE foam tape, solvent acrylic adhesive.

Technical details

Adhesion at 180° on stainless steel: 12 N/cm.
 Tensile strength: 65 N/10 mm².
 Density: 100 kg/m³.
 Operating temperature: -20 °C to +120 °C.
 Application temperature: +15 °C to +30 °C.
 Bonding period (at 23 °C): 24 hr.

Application(s)

Assembly operations for which a good load bearing capacity is required.
 Hanging mirrors, rods and mouldings.
 Signs and panels.

LOGISTIC INFORMATION

Packaging



Plastic film

Height (cm) : 15
 Length (cm) : 15
 Depth (cm) : 1,9
 Net weight (kg) : 0,09
 Gross weight (kg) : 0,092



Outer package 1



x 14.00

Carton box

Height (cm) : 16
 Length (cm) : 30
 Depth (cm) : 16
 Net weight (kg) : 1,02
 Gross weight (kg) : 1,17



Outer package 2



x 1428.00

Pallet

Height (cm) : 120
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 120
 Gross weight (kg) : 130

