

Nickel-plated steel concrete hanger screw (x 50)



Characteristics

Drilling Ø (mm) : **5**
 Eyelet Ø (mm) : **5.5**
 Screw length (mm) : **70**
 Screw useful length (mm) : **32**
 Tear-out resistance concrete (kg) : **70**
 Quantity per box : **50**

Materials

- ✓ Solid materials
- ✓ Concrete
- ✓ Wood

Benefits

- Economical: no dowel required.
- Practical: installation tool can be used with an electric screwdriver.
- Installation tool supplied.

GENERAL INFORMATION

Technical details

Chrome- and nickel-plated steel with full thread.

Application(s)

For fixing cable trays and suspension in concrete and wood.
 For use with chains (BIZ 710 171, BIZ 710 172, BIZ 710 174), S hooks (BIZ 710 170, BIZ 710 173), cables (BIZ 710 350, BIZ 710 351, BIZ 710 352, BIZ 710 353), straight rods, steel wire, carabinas, etc.

Instructions

1. Drill to Ø 5 mm.
2. Screw into concrete using the installation tool provided.
3. The Ø 5.5 mm eyelet can be used for collars, wire, S hooks (Ø 4 mm maximum), straight rods.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 4
 Length (cm) : 13,5
 Depth (cm) : 8,8
 Net weight (kg) : 0,595
 Gross weight (kg) : 0,599



3 700420 321132

Outer package 1



Carton box

x 12.00



3 700420 360117