



HSS metal drill bit Ø 7 x 109 mm



Characteristics

Ø (mm) : 7  
 Total length (mm) : 109  
 Useful length (mm) : 69  
 Quantity : *Per unit*

Materials

☑ Metal

Benefits

Its construction and flared shape offer several advantages:

- No blocking in the tool.
- Less friction.
- Extended life time.
- Excellent elasticity.

GENERAL INFORMATION

■ Technical details

Cylindrical shank.  
 Monoblock head.  
 Helix angle between 23° and 33°.

■ Application(s)

For drilling copper, brass, nickel, zinc and plastics.  
 Particularly suitable for 600 N/mm<sup>2</sup> carbon steels, standard 800 N/mm<sup>2</sup> steels and standard 900 N/mm<sup>2</sup> steel alloys.  
 Not suitable for drilling in stainless steel.

LOGISTIC INFORMATION

📦 Packaging



Plastic tube

Height (cm) : 0,8  
 Length (cm) : 20,5  
 Depth (cm) : 3,5  
 📦 Net weight (kg) : 0,027  
 📦 Gross weight (kg) : 0,034



📦 Outer package 1



Carton box

Height (cm) : 18,5  
 Length (cm) : 35,5  
 Depth (cm) : 30  
 📦 Net weight (kg) : 5,4  
 📦 Gross weight (kg) : 7,215

