



HSS metal drill bit Ø 6.5 x 101 mm (x 1)



Characteristics

Ø (mm) : **6.5**
 Total length (mm) : **101**
 Useful length (mm) : **63**
 Quantity : **Per unit**

Materials

☑ Metal

Benefits

Its construction and flared shape offer several advantages:

- No blocking in the tool.
- Less friction.
- Extended life time.
- Excellent elasticity.



GENERAL INFORMATION

■ Technical details

Cylindrical shank.
 Monoblock head.
 Helix angle between 23° and 33°.

■ Application(s)

For drilling copper, brass, nickel, zinc and plastics.
 Particularly suitable for 600 N/mm² carbon steels, standard 800 N/mm² steels and standard 900 N/mm² steel alloys.
 Not suitable for drilling in stainless steel.



LOGISTIC INFORMATION

■ Packaging



Plastic tube

Height (cm) : 19,7
 Length (cm) : 20,5
 Depth (cm) : 3,5
 📦 Net weight (kg) : 0,021
 📦 Gross weight (kg) : 0,028



■ Outer package 1



Carton box

Height (cm) : 18,5
 Length (cm) : 35
 Depth (cm) : 3,5
 📦 Net weight (kg) : 4,16
 📦 Gross weight (kg) : 5,975



x 200