



Connexion SQUALE 25 kit for sealed connection up to 4 conductors of wire 6 mm²

Quick, waterproof, efficient



Caracteristics

Capacity 1 conductor (mm²): **120-240**

Capacity 2 conductors (mm²): **6-50**

Capacity 3 conductors (mm²): **6-35**

Capacity 4 conductors (mm²): **4-35**

Dimensions (mm): **210 x 65**

Norms

☑ EN 50393

☑ IP X8

Benefits

- IPX8 for immersed installations.
- Full range dedicated to residential and tertiary.
- Non toxic.

Compliance marks



GENERAL INFORMATION

Technical details

Voltage: 0.6 to 1 kV.

Application(s)

For connecting, insulating, sealing and protecting copper electrical cables.

Supplied with cable centring device and cable ties for holding conduits.

Instructions

1. Strip and connect the cables.
2. Insert the separator and centre the cables in the enclosure.
3. Close the enclosure and lock in the conduits.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 10

Length (cm) : 23

Depth (cm) : 11

Net weight (kg) : 0,491

Gross weight (kg) : 0,491



3 780420 325862

Outer package 1



x 24

Carton box

Height (cm) : 44

Length (cm) : 50

Depth (cm) : 38

Net weight (kg) : 11,784

Gross weight (kg) : 12,41



3 780420 366386

Outer package 2



x 192

Pallet

Height (cm) : 105

Length (cm) : 80

Depth (cm) : 120

Net weight (kg) : 99,28

Gross weight (kg) : 130



3 780420 381983