

Terminal blocks 25 mm² 101A white polypropylene (x 10)

Characteristics

Colour : **White**
 Section (mm²) : **25**
 Current (A) : **101**
 Voltage (V) : **400**
 Length (mm) : **204**
 Height (mm) : **24**
 Depth (mm) : **32**
 Quantity : **10**

Norms

- ✓ EN 60998-2-1, NF
- ✓ EN 60695-2
- ✓ IP 20

Benefits

- Ultra-flexible blocks.
- Can be separated in 1.5 turns without the use of tools.

Compliance marks



ENVIRONMENTAL PROFILE



¹ Net volume of freshwater consumed - ² Total primary energy use during the life cycle - ³ Abiotic resource depletion - elements

* Data verified and published on PEP ecopassport

GENERAL INFORMATION

Description

12-way polypropylene connector strips.
Supplied with screws engaged at 1/3.

Technical details

Glow wire test: 960 °C.

LOGISTIC INFORMATION

Packaging



Plastic film

Height (cm) : 23
 Length (cm) : 5
 Depth (cm) : 15
 Net weight (kg) : 1,23
 Gross weight (kg) : 1,25



Outer package 1



x 5.00

Carton box

Height (cm) : 26
 Length (cm) : 23
 Depth (cm) : 18
 Net weight (kg) : 6,13
 Gross weight (kg) : 6,27

