



# Connexion SQUALE 6 kit for sealed connection up to 4 conductors of wire section 6 mm<sup>2</sup>

**Quick, waterproof, efficient**



## Characteristics

Capacity 1 conductor (mm<sup>2</sup>): **1.5-50**  
 Capacity 2 conductors (mm<sup>2</sup>): **1.5-10**  
 Capacity 3 conductors (mm<sup>2</sup>): **1.5-10**  
 Capacity 4 conductors (mm<sup>2</sup>): **1.5-6**  
 Dimensions (mm): **105 x 55**

## Norms

- ⊙ EN 50393
- ⊙ IP X8

## Benefits

- IPX8 for immersed installations.
- Full range dedicated to residential and tertiary.
- Non toxic.

## Compliance marks



## GENERAL INFORMATION

### Technical details

Voltage: 0.6 to 1 kV.

### Application(s)

For connecting, insulating, sealing and protecting copper electrical cables.  
 Supplied with cable centring device and cable ties for holding conduits.

### Instructions



1. Strip and connect the cables.
2. Insert the separator and centre the cables in the enclosure.
3. Close the enclosure and lock in the conduits.

 LOGISTIC INFORMATION

 Packaging



**Carton box**

Height (cm) : 11  
 Length (cm) : 12  
 Depth (cm) : 7  
 Net weight (kg) : 0,14  
 Gross weight (kg) : 0,14





 Outer package 1



x 100

**Carton box**

Height (cm) : 44  
 Length (cm) : 50  
 Depth (cm) : 38  
 Net weight (kg) : 14  
 Gross weight (kg) : 14,56





 Outer package 2



x 800

**Pallet**

Height (cm) : 105  
 Length (cm) : 80  
 Depth (cm) : 120  
 Net weight (kg) : 116,48  
 Gross weight (kg) : 147

