TECHNICAL SHEET BIZ 710 308

Junction SQUALE D6 kit sealed connection 1 x 5 entry screw connector wire up to 5 x 4 mm²



Quick and watertight, the addition to your squale range for junction boxes



Caracteristics

Main cable capacity (mm^2) : Up to 5 x 1.5 to 6 Junction cable capacity (mm^2) : Up to 5 x 1.5 to 4

Main cable maximum Ø (mm): 22.5 Junction cable maximum Ø (mm): 18.5 Dimensions (mm): 138 x 60 x 37

Benefits

- IPX8 watertightness for your junctions.
- Easy and quick installation.
- Comprehensive product with connection system.
- Non toxic.

Norms

GENERAL INFORMATION

Technical details

Voltage: 0.6 to 1 kV. Supplied with 5-input connection system and 4 cable ties for perfect watertightness.

Application(s)

For connecting, insulating, sealing and protecting copper electrical cables.

Ideal in outdoor, damp and immersed environments.

Instructions

- 1. Connect to the brass terminal connection system provided.
- 2. Open the SQUALE and insert the terminal system at required position.
- 3. Close the SQUALE and tighten the cable exits with the cabling clamps.



BIZ 710 308 TECHNICAL SHEET

DESCRIPTION LOGISTIC INFORMATION

Packaging



Carton box

Height (cm): 16 Length (cm): 9 **Depth (cm):** 5,5 **♣ Net weight (kg):** 0,165




Outer package 1

x 70.00

Carton box

Height (cm): 44 Length (cm): 50 **Depth (cm):** 38



a Gross weight (kg): 0,165



Pallet

Height (cm): 105 Length (cm): 80 Depth (cm): 120

Net weight (kg): 92,4
Gross weight (kg): 97,6



