

Push wire connectors CHRISTA'L MINI 2 way (x 100)



Characteristics

Number of inputs : **2**
 Colour : **Purple**
 Quantity per box : **100**

Benefits

- Test point for quick checking of the connection.

Compliance marks



ENVIRONMENTAL PROFILE



¹ Net volume of freshwater consumed - ² Total primary energy use during the life cycle - ³ Abiotic resource depletion - elements

* Data verified and published on PEP ecopassport

GENERAL INFORMATION

Description

Christa'L Mini push-in wire connectors.

Technical details

Self-extinguishing V0 approved automatic connection terminals.
 Glow wire test 960 °C < 5 s (NF EN 60 998-2-2).
 Operating temperature : -25 °C to +50 °C.
 For solid wires from 1.5 to 2.5 mm².
 Material: polycarbonate colored body and polyamide 6.6.
 Voltage: 400 V.
 Intensity: 24 A.

Instructions

1. Stripping: 11 mm.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 12,5
 Length (cm) : 9,8
 Depth (cm) : 5,2
 Net weight (kg) : 0,08
 Gross weight (kg) : 0,15



3 780428 341684

Outer package 1



x 72.00

Carton box

Height (cm) : 37,5
 Length (cm) : 39
 Depth (cm) : 31
 Net weight (kg) : 10,8
 Gross weight (kg) : 10,1



3 780428 347895

Outer package 2



x 1296.00

Pallet

Height (cm) : 126
 Length (cm) : 120
 Depth (cm) : 80
 Gross weight (kg) : 194



3 781395 153902