

Push wire connectors CHRISTA'L MINI 5 way (x 100)



Characteristics

Number of inputs : **5**

Colour : **Blue**

Quantity per box : **100**

Benefits

- Test point for quick checking of the connection.

Compliance marks



ENVIRONMENTAL PROFILE



¹ Net volume of freshwater consumed - ² Total primary energy use during the life cycle - ³ Abiotic resource depletion - elements

* Data verified and published on PEP ecopassport

GENERAL INFORMATION

Description

Christa'L Mini push-in wire connectors.

Technical details

Self-extinguishing V0 approved automatic connection terminals.

Glow wire test 960 °C < 5 s (NF EN 60 998-2-2).

Operating temperature : -25 °C to +50 °C.

For solid wires from 1.5 to 2.5 mm².

Material: polycarbonate colored body and polyamide 6.6.

Voltage: 400 V.

Intensity: 24 A.

Instructions

1. Stripping: 11 mm.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 12,5

Length (cm) : 9,8

Depth (cm) : 8

Net weight (kg) : 0,18

Gross weight (kg) : 0,25



3 700420 341611

Outer package 1



x 48.00

Carton box

Height (cm) : 37

Length (cm) : 39

Depth (cm) : 31

Net weight (kg) : 15

Gross weight (kg) : 12,28



3 700420 347125

Outer package 2



x 864.00

Pallet

Height (cm) : 125

Length (cm) : 120

Depth (cm) : 80

Gross weight (kg) : 221



3 701395 153933