


PERFORMANCE BRANDS

Code	PB10C-BLK	
Standard	EN ISO 20345:2011 S3 HRO HI CI SRC	
Name / Description	Dual Density Rubber Derby Boot c/w Cap	
Weight	900 grams	
Colour	Black <i>*Available in sizes 6.5 and 10.5</i>	


Sizes	3	4	5	6*	7	8	9	10*	11	12	13	14
-------	---	---	---	----	---	---	---	-----	----	----	----	----

Properties	<p>Upper: Breathable, Full Grain Leather with Leather Tongue and Collar. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Abrasion Resistant, Moisture Wicking Textile.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Stainless Steel Midsole – Min. 1100N.</p> <p>Sole Unit: Dual Density Rubber/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p>
------------	--

Areas of Application	<p>The PB10C is suitable for most heavy duty applications. Typical applications include digging, groundworks, construction, engineering, utilities, and rail. The overcap makes it perfect for jobs which involve kneeling as the cap prevents the leather from being worn away from the toe of the boot.</p>
----------------------	---

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	<p>S3 HRO HI CI SRC</p>	 <p>PRODUCT PERFORMANCE PASSION</p>
----------	--	---------------------------------	---

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk </p>
---------	---