




EMN001



Stair case time lag switch

Technical characteristics

Architecture

Fixing mode	Din-Rail
-------------	----------

Configuration

Switch mode	NO contact
-------------	------------

Main electrical features

Rated operational voltage Ue	230 V
Frequency	50/60

Electric current

Acceptable current rating with AC1	16 A
------------------------------------	------

Dimensions

Depth of installed product	64 mm
Width of installed product	17.5 mm

Power

Max. power with fluo uncompensated lamps	3600 VA
Power consumed	1 VA
Total power loss under IN	2 W
Power dissipation per coil	0.25 W

Power supply

Supply voltage	230 V
----------------	-------

Fluorescent bulbs control

Max. power with fluorescent parallel lamps	1000 VA
--	---------

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

Installation, mounting

Mounting type	din-Rail
---------------	----------

Connection

Connection cross-sect. flexible conductor	1 / 6mm ²
Connection cross-sect. rigid cable	1,5 / 10mm ²
Type of connection	with screw
Connection type	3 and 4 wires
Number of contacts	1

Type of contacts	1NO
Type of connection	with screw terminals
Settings	
Time delayed range	30s / 10min
Safety	
Protection index IP	IP20
Use conditions	
Operating temperature	-10...55 °C