

OBX-
OBX-

OBX-

Features/Benefits:

- ✓ Strong reliable fixing for wood and wallplugs
- ✓ Specially designed profile thread for quick assembly and longlasting hold
- ✓ Wax coat for faster, easier installation saving energy

3.0mm Dia.

WS-3.0x20 (200pk) OBX-WS-4.5x25 (200pk)

WS-3.0x25 (200pk) OBX-WS-4.5x40 (200pk)

OBX-WS-4.5x50 (200pk)

3.5mm Dia.

WS-3.5x20 (200pk)

OBX-WS-3.5x25 (200pk) OBX-WS-5.0x60 (100pk) OBX-

WS-3.5x30 (200pk) OBX-WS-5.0x75 (100pk)

4.0mm Dia.

OBX-WS-4.0x40 (200pk)

OBX-WS-4.0x50 (200pk)

Application:

- ⊕ Fixing electrical accessories into solid wood, timber panels or laminated timber

8

Steel thickness:
Up to 2.5mm



Steel thickness:
Up to 3.0mm



ORBIX STANDARD WOOD SCREW

USE FOR

- ⊕ Direct fixing into wood
- ⊕ Direct fixing into standard wallplug



Key Feature:

Extra sharp tip for faster installation.
Countersunk head.

ORBIX PAN HEAD

USE FOR

- ⊕ Where space is tight – a range of self-drilling screws with a smaller diameter head.



Key Feature:

Every screw has a **BRAND NEW DRILL BIT** – built in! Always sharp, always the right size.