

ORBIX FOR METAL


KEY FEATURE:

Every screw has a BRAND NEW
DRILLBIT - built in! Always
sharp, always the right size



USE FOR

Self Drilling/Self tapping into metal

		Steel thickness
OBX-STD-4.8 X 16		Up to 2.5mm
OBX-HD-5.5 X 20		Up to 3.5mm
OBX-HD-5.5 X 40		Up to 3.5mm

Features/Benefits:

- ⊕ No Pre-drilling required ✓
- ⊕ No Nuts, Bolts, Spanners etc. ✓
- ⊕ No Changing drill/drive bits - Standard PZ2 recess ✓
- ⊕ Can be removed and re-used ✓
- ⊕ Unique Orbix wafer head - will not snag or chafe cables ✓
- ⊕ Point caps available to protect cables when installed ✓

Application

- ⊕ Faster joining of cable tray, cable trunking, trunking lid etc.
- ⊕ Armoured Cable Cleats
- ⊕ Mounting din rail and accessories in control panels
- ⊕ Speedy fixing of earth tags to galvanised trunking/boxes
- ⊕ **PLUS ENDLESS APPLICATIONS THAT REQUIRE A FAST, ONE-SHOT JOINING OF THIN STEEL**



For further information and samples please call 0800 032 5008