



EH010



**IP20**

## Daily time switch 1 channel, 16A, 1 module

### Technical characteristics

#### Architecture

|             |          |
|-------------|----------|
| Fixing mode | Din-Rail |
|-------------|----------|

#### Configuration

|             |            |
|-------------|------------|
| Switch mode | NO contact |
|-------------|------------|

#### Main electrical features

|           |    |
|-----------|----|
| Frequency | 50 |
|-----------|----|

#### Dimensions

|                             |       |
|-----------------------------|-------|
| Depth of installed product  | 60 mm |
| Height of installed product | 80 mm |
| Width of installed product  | 18 mm |

#### Power

|                               |        |
|-------------------------------|--------|
| Power consumed                | 0.5 VA |
| Power consumption (operation) | 0.5 VA |
| Total power loss under IN     | 1 W    |
| Power dissipation per coil    | 0.5 W  |

#### Incandescent bulbs control

|                                    |       |
|------------------------------------|-------|
| Max. power with incandescent lamps | 900 W |
|------------------------------------|-------|

#### Installation, mounting

|               |          |
|---------------|----------|
| Mounting type | din-Rail |
|---------------|----------|

#### Connection

|                                           |                         |
|-------------------------------------------|-------------------------|
| Connection cross-sect. flexible conductor | 1 / 6mm <sup>2</sup>    |
| Connection cross-sect. rigid cable        | 1,5 / 10mm <sup>2</sup> |
| Type of connection                        | with screw              |
| Number of contacts                        | 1                       |
| Type of contacts                          | 1 changeover            |
| Type of connection                        | with screw terminals    |

#### Settings

|                             |                      |
|-----------------------------|----------------------|
| Summer / Winter time change | manual               |
| Shortest switching time     | 15 mn                |
| Type of programming         | analog               |
| Programming cycle           | 24H                  |
| Setting                     | Setting via day dial |

**Equipment**

|                        |         |
|------------------------|---------|
| Number of channels     | 1       |
| Supply failure reserve | without |

**Use**

|       |       |
|-------|-------|
| Cycle | daily |
|-------|-------|

**Safety**

|                     |      |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

**Use conditions**

|                       |             |
|-----------------------|-------------|
| Operating temperature | -10...55 °C |
| Working accuracy      | 1           |