



WMSSU83FON

13A FCU Switched with LED Indicator and Flex Outlet

Technical characteristics

Configuration

| | |
|-------------|-------|
| Switch mode | 2pole |
|-------------|-------|

Main electrical features

| | |
|---------------|------|
| Rated current | 13 A |
|---------------|------|

Fuse

| | |
|------|------------------------------|
| Fuse | with ceramic fine fuse F 13A |
|------|------------------------------|

Dimensions

| | |
|--------|---------|
| Depth | 30.3 mm |
| Height | 86 mm |
| Width | 86 mm |

Materials

| | |
|----------|-------------------|
| Colour | white |
| Material | Urea-formaldehyde |

Cable

| | |
|--------|------------------------------|
| Wiring | with double earth connection |
|--------|------------------------------|

Scope of delivery

| | |
|-----------|-----------------------------------|
| Component | with 2 fixing screws M3.5 x 30 mm |
|-----------|-----------------------------------|

Equipment

| | |
|----------|-------------------------|
| Lighting | with control LED for ON |
|----------|-------------------------|

Standards

| | |
|----------|-----------|
| Standard | BS 1363-4 |
|----------|-----------|

Safety

| | |
|------------|-----------------------------|
| Protection | to protect downstream loads |
|------------|-----------------------------|