

PRODUCT-DETAILS

## **OT16F3C**OT16F3C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT16F3C
Product ID	1SCA104816R1001
EAN	6417019389608
Catalog Description	OT16F3C CHANGE-OVER SWITCH
Long Description	OT16F3C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Open transition

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301054M0001

Dimensions	
Product Net Width	70 mm
Product Net Height	68 mm
Product Net Depth / Length	68 mm
Product Net Weight	70 lb
	0.25 kg

Technical	
Rated Operational	(380 415 V) 16 A
Current AC-21A (I <sub>e</sub> )	(500 V) 16 A
Ontad Operational	(690 V) 16 A
Rated Operational Current AC-22A (I <sub>e</sub> )	(380 415 V) 16 A (500 V) 16 A
Continue Ela (ie)	(690 V) 16 A
Rated Operational	(380 415 V) 16 A
Current AC-23A (I <sub>e</sub> )	(500 V) 16 A
	(690 V) 10 A
Rated Operational	(380 415 V) 7.5 kW
Power AC-23A (P <sub>e</sub> )	(500 V) 7.5 kW (690 V) 7.5 kW
Conventional Free-air	q = 40 °C 25 A
Thermal Current (I <sub>th</sub> )	q - 40 C L 3 A
Conventional Thermal	Fully Enclosed 25 A
Current (I <sub>the</sub> )	Tully Effelosed Es 70
Rated Impulse	8 kV
Withstand Voltage (U <sub>imp</sub>	O KV
)	
Rated Insulation Voltage	750 V
(U <sub>i</sub> )	.50 .
Rated Operational	750 V
Voltage	
Rated Short-time	for 1 s 0.5 kiloampere rms
Withstand Current (I <sub>cw</sub> )	
Power Loss	0.3 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating	Mechanism on Top of the Switch
Mechanism	·
Distance Between	Standard
Phases	
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	0.75 10 mm²
Degree of Protection	Front IP20
Technical UL/CSA	
Horsepower Rating	(acc. to UL 200 V) 3 Hp
UL/CSA	(acc. to UL 480 V) 10 Hp
	(acc. to UL 208 V) 3 Hp
	(acc. to UL 240 V) 5 Hp
Annual Dating III /CCA	(acc. to UL 600 V) 10 Hp
Ampere Rating UL/CSA	16 A
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303019D0201
Instructions and	1SCC301054M0001
Manuals	
RoHS Information	1SCC301183D0201

Package Level 1 Units	1 piece
Package Level 1 Width	80 mm
Package Level 1 Depth / Length	108 mm
Package Level 1 Height	79 mm
Package Level 1 Gross Weight	0.25 kg
Package Level 1 EAN	6417019389608

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	3171260

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

