

140 lb

PRODUCT-DETAILS

## **OT100F3C**OT100F3C CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT100F3C
Product ID	1SCA105008R1001
EAN	6417019391397
Catalog Description	OT100F3C CHANGE-OVER SWITCH
Long Description	OT100F3C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Open transition
Popular Downloads	
•	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203
Dimensions	
Product Net Width	140 mm
Product Net Height	100 mm
Product Net Depth / Length	86 mm
Product Net Weight	0.9 kg

Technical	
Rated Operational	(380 415 V) 100 A
Current AC-21A (I <sub>a</sub> )	(380 415 V) 100 A (500 V) 100 A
	(690 V) 100 A
Rated Operational	(380 415 V) 100 A
Current AC-22A (I <sub>e</sub> )	(500 V) 100 A (690 V) 100 A
Rated Operational	(380 415 V) 80 A
Current AC-23A (I <sub>e</sub> )	(500 V) 60 A (690 V) 40 A
Rated Operational	(380 415 V) 37 kW
Power AC-23A (P <sub>e</sub> )	(500 V) 37 kW (690 V) 37 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 115 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 115 A
Rated Impulse	8 kV
Withstand Voltage (U <sub>imp</sub> )	S.K.
Rated Insulation Voltage (U <sub>i</sub> )	750 V
Rated Operational Voltage	750 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 2.5 kiloampere rms
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	10 70 mm²
Degree of Protection	Front IP20
Technical UL/CSA	
Horsepower Rating	(acc. to UL 200 V) 30 Hp
UL/CSA	(acc. to UL 208 V) 30 Hp
	(acc. to UL 240 V) 30 Hp
	(acc. to UL 480 V) 50 Hp (acc. to UL 600 V) 50 Hp
Ampere Pating III /CSA	
Ampere Rating UL/CSA	100 A
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303021D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301183D0201

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	102 mm	
Package Level 1 Depth / Length	205 mm	
Package Level 1 Height	103 mm	
Package Level 1 Gross Weight	0.9 kg	
Package Level 1 EAN	6417019391397	

Classifications		
Object Classification Code	Q	
ETIM 5	EC000216 - Switch disconnector	
ETIM 6	EC000216 - Switch disconnector	
ETIM 7	EC000216 - Switch disconnector	
UNSPSC	39122233	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Sweden)	3171265	

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$ 

