

PRODUCT-DETAILS

LFH-SPSS25/25M

SS OVERBRAID LFH-SP COND NC25 25M



General Information

Extended Product Type	LFH-SPSS25/25M
Product ID	7TCA296100R0021
EAN	5020963050480
Catalog Description	SS OVERBRAID LFH-SP COND NC25 25M
Long Description	Low Fire Hazard, Medium Flexibility Conduit with Stainless Steel Overbraid, Nominal Conduit Size 25mm, Outside Diameter 26mm, Inside Diameter 21.4mm, Static Bend Radius 110mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Ordering

EAN	5020963050480
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	20.01 lb 9.075 kg
--------------------	----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with LFH Jacket and Stainless Steel Overbraid
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	110 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248547

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TK001224
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPSS25/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

