

PRODUCT-DETAILS

S32/25M

25M X S32 CONDUIT



General Information

Extended Product Type	S32/25M
Product ID	7TCA296010R0118
EAN	5020963001437
Catalog Description	25M X S32 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 32mm, Outside Diameter 32.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963001437
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	25.35 lb
	11.497 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	17 in
	432 mm

Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	28.1 mm
Material	Galvanized Steel
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	32.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	60 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251523

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S32/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

