

List No. NM1406L

NH / NM / NMX

14 Way Consumer Unit Main Switch 100A



- 14W Main switch only consumer unit
- Includes a 100A main switch with twin line and neutral supply terminals and a 100A fixed busbar assembly
- Accepts all Wylex miniature final circuit protection devices; MCBs, RCBOs and AFDDs
- Accepts the Wylex miniature type 2 SPD, NMT2SPD3W/1
- Constructed from a full metal enclosure with curved visor and temporary locking facility

Mounting method Surface mounted (plaster) Number of phases 1 Protection Miniature- / earth leakage circuit breaker Total number of groups 1 Number of poles main switch 2 Main switch rated current 100 A Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14	Product Specification Data	Revision Date: 14/06/2022
Protection Miniature- / earth leakage circuit breaker Total number of groups 1 Number of poles main switch 2 Main switch rated current 100 A Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch rating Mini switch rating Mini switch rating Mini switch rating Mini switch rating Mo Over voltage include a care the leakage circuit breaker 100 A Over voltage include steel and so A Total final circuit modular ways Mini switch rating Mini switch rating	Mounting method	Surface mounted (plaster)
Total number of groups 1 Number of poles main switch 2 Main switch rated current 100 A Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes VESE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed	Number of phases	1
Number of poles main switch 2 Main switch rated current 100 A Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed	Protection	Miniature- / earth leakage circuit breaker
Main switch rated current 100 A Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Total number of groups	1
Over voltage protection No Material housing Steel Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Number of poles main switch	2
Material housing Degree of protection (IP) IP2XC Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth Extension possible No With transparent cover No Lockable Product Standard/s Frequency 50 Hz CE Conformity Yes WEEE Symbol UKCA Conformity Yes UKCA Conformity Amperage Operating Voltage Type of Current AC Consumer Unit Type Main switch only Midth Midth A43 mm Steel IP2XC IP2XC Hmm 16 House Height 121 mm 121 mm No	Main switch rated current	100 A
Degree of protection (IP) Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Product Standard/s Frequency 50 Hz CE Conformity Yes WEEE Symbol UKCA Conformity Yes UKCA Conformity Yes Amperage 100 A Operating Voltage Type of Current AC Consumer Unit Type Main switch rating Main switch rating Midth Midth Midth Main switch rating Midth 16 16 100 A 16 101 Mm 121 mm 12	Over voltage protection	No
Height 261 mm Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Material housing	Steel
Width 343 mm Width in number of modular spacings 16 Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Degree of protection (IP)	IP2XC
Width in number of modular spacings16Depth121 mmExtension possibleNoWith transparent coverNoLockableYesProduct Standard/sBS EN 61439-3Frequency50 HzCE ConformityYesWEEE SymbolYesUKCA ConformityYesAmperage100 AOperating Voltage230 VType of CurrentACConsumer Unit TypeMain switch onlyTotal final circuit modular ways14Busbar typeFixedMain switch rating100 A	Height	261 mm
Depth 121 mm Extension possible No With transparent cover No Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Operating Voltage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Main switch rating 120 Mo	Width	343 mm
Extension possible With transparent cover Lockable Product Standard/s Frequency CE Conformity WEEE Symbol UKCA Conformity Yes UKCA Conformity Yes Amperage Operating Voltage Type of Current Consumer Unit Type Main switch only Total final circuit modular ways Min switch rating No No No No No No Yes BS EN 61439-3 Frequency 50 Hz Yes UKCA Conformity Yes 100 A Conformity AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating	Width in number of modular spacings	16
With transparent coverNoLockableYesProduct Standard/sBS EN 61439-3Frequency50 HzCE ConformityYesWEEE SymbolYesUKCA ConformityYesAmperage100 AOperating Voltage230 VType of CurrentACConsumer Unit TypeMain switch onlyTotal final circuit modular ways14Busbar typeFixedMain switch rating100 A	Depth	121 mm
Lockable Yes Product Standard/s BS EN 61439-3 Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Fixed Main switch rating 100 A	Extension possible	No
Product Standard/s Frequency 50 Hz CE Conformity Yes WEEE Symbol UKCA Conformity Yes UKCA Conformity Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Main switch rating BS EN 61439-3 BS EN 61439-3 BUS EN 61439-3 BUS EN 61439-3 BUS EN 61439-3 BUS EN 61439-3 AC Fixed Main switch only Fixed Main switch rating	With transparent cover	No
Frequency 50 Hz CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Fixed Main switch rating 100 A	Lockable	Yes
CE Conformity WEEE Symbol Yes UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Main switch rating 100 A	Product Standard/s	BS EN 61439-3
WEEE Symbol UKCA Conformity Yes Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Fixed Main switch rating 100 A	Frequency	50 Hz
UKCA Conformity Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Main switch rating 100 A	CE Conformity	Yes
Amperage 100 A Operating Voltage 230 V Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	WEEE Symbol	Yes
Operating Voltage Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways Busbar type Fixed Main switch rating 100 A	UKCA Conformity	Yes
Type of Current AC Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Amperage	100 A
Consumer Unit Type Main switch only Total final circuit modular ways 14 Busbar type Fixed Main switch rating 100 A	Operating Voltage	230 V
Total final circuit modular ways Busbar type Fixed Main switch rating 14 100 A	Type of Current	AC
Total final circuit modular ways Busbar type Fixed Main switch rating 14 100 A	Consumer Unit Type	Main switch only
Main switch rating 100 A		14
5	Busbar type	Fixed
Main switch final circuit modular ways 14	Main switch rating	100 A
	Main switch final circuit modular ways	14

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)

Revision Date: 14/06/2022

Colour RAL 9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

