

**Product Code:** VPSC536GY

**Description:** 13A Ingot 2 Gang Double Pole Switched Socket Outlet



### General Information

<b>Plate Dimensions</b>	146mm (W) x 88mm (H) x 8mm (D)	
<b>Dimensions With Gasket</b>	149mm (W) x 91mm (H) x 9mm (D)	
<b>Plate Design &amp; Finish</b>	Victorian Satin Chrome	
<b>Insert &amp; Gasket Colour</b>	Grey	
<b>Materials</b>	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon	Insert & Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	13A	
<b>Plate Fixing Centres</b>	120.6mm	
<b>Terminal Size</b>	5mmø	
<b>Terminal Torque</b>	2.0Nm	
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>	
<b>Double Pole</b>	Yes	
<b>Twin Earth Terminals</b>	Yes	
<b>Ingress Protection</b>	IP20	
<b>Back Box Depth</b>	25mm Minimum	
<b>Termination Type</b>	Screw	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	10 Years	
<b>Standards</b>	BS 1363-2: 2016 +A1: 2018	

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621