Main

Range	Multi9
Product or component type	Add-on residual current devices
Device short name	Vigi C60
Range compatibility	Multi9 (Multi9 C60) C60N Multi9 (Multi9 C60) C60L Multi9 (Multi9 C60) C60H Multi9 (Multi9 C60) C60CTRL
Poles description	3P
[In] rated current	63 A conforming to EN/IEC 61009-1
Network type	AC
Network frequency	50 Hz
[Ue] rated operational voltage	400/415 V AC 50 Hz
Earth-leakage sensitivity	300 mA conforming to EN/IEC 61009-1
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
9 mm pitches	7

Complementary

Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50 Hz conforming to EN/IEC 61009-1
[Uimp] rated impulse withstand voltage	4 kV conforming to EN/IEC 61009-1
Local signalling	Fault indication
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	By screws
Height	87 mm
Width	63 mm
Depth	74 mm
Net weight	210 g

Colour	Grey
Connections - terminals	Tunnel type terminal (bottom) 135 mm² - rigid Tunnel type terminal (bottom) 125 mm² - flexible Tunnel type terminal (bottom) 125 mm² - flexible with ferrule
Wire stripping length	14 mm for bottom connection
Tightening torque	3.5 N.m bottom
Environment	
Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3 conforming to IEC 61009
Electromagnetic compatibility	8/20 μs impulse withstand, 250 A conforming to EN/IEC 61009-1
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-4060 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	10 cm
Package 1 Length	15 cm
Package 1 Weight	231 g
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.949 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty

18 months

Recommended replacement(s)