

# Product datasheet

Specifications



## iC60H2 - earth leakage circuit breaker - 2P - C curve - 20 A - 30m A - 240 V

Local distributor code: 402639309 A9D11220

EAN Code : 3606480558740

### Main

Circuit breaker application	Distribution
Range	Acti9
Product name	Acti9 iC60 RCBO
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Device short name	iC60H2 RCBO
Poles description	2P
[In] rated current	20 A at 50 °C
Earthing system	IT TN TT
Curve code	C
Earth-leakage sensitivity	30 mA
Breaking capacity	10000 A Icn at 230/240 V AC 50/60 Hz

### Complementary

Neutral position	Left
Number of protected poles	2
Device location in system	Outgoer
Network frequency	50 Hz
Network type	AC
Trip unit technology	Thermal-magnetic
[Ue] rated operational voltage	230/240 V AC 50/60 Hz
Residual current tripping technology	Voltage dependent
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
[Icw] rated short-time withstand current	Icw: 250 A during 8/20 µs impulse withstand
[Ics] rated service breaking capacity	7500 A at 230/240 V AC 50/60 Hz
Limitation class	3

<b>[Ui] rated insulation voltage</b>	400 V AC 50/60 Hz
<b>[Uimp] rated impulse withstand voltage</b>	4 kV
<b>Surge current</b>	250 A
<b>Suitability for isolation</b>	Yes
<b>Contact position indicator</b>	Yes
<b>Control type</b>	Toggle
<b>Local signalling</b>	ON/OFF indication
<b>Mounting mode</b>	Clip-on
<b>Mounting support</b>	DIN rail
<b>Comb busbar and distribution block compatibility</b>	NO
<b>9 mm pitches</b>	4
<b>Height</b>	110 mm
<b>Width</b>	36 mm
<b>Depth</b>	75.5 mm
<b>Net weight</b>	332 g
<b>Colour</b>	White
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	5000 cycles
<b>Provision for padlocking</b>	Padlockable with padlock Ø 4 mm
<b>Locking options description</b>	ON/OFF locking facilities
<b>Connections - terminals</b>	Screw clamp terminal (top) 1...25 mm <sup>2</sup> rigid without cable end Screw clamp terminal (top) 1...16 mm <sup>2</sup> flexible Screw clamp terminal (bottom) 1...16 mm <sup>2</sup> rigid without cable end Screw clamp terminal (bottom) 1...10 mm <sup>2</sup> flexible
<b>Wire stripping length</b>	Power circuit: 13 mm for bottom connection Power circuit: 14 mm for top connection
<b>Tightening torque</b>	Power circuit: 3.5 N.m top Power circuit: 2 N.m bottom
<b>Earth-leakage protection</b>	Integrated

## Environment

<b>Standards</b>	AS/NZS 61009.1 IEC 61009-2-2 IEC 61009-1
<b>IP degree of protection</b>	IP20
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-15...60 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.5 cm
<b>Package 1 Width</b>	9.5 cm

Package 1 Length	1.8 cm
Package 1 Weight	268.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	27
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.732 kg
Unit Type of Package 3	P12
Number of Units in Package 3	864
Package 3 Height	70.0 cm
Package 3 Width	120.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	243.552 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<a href="#">REACh Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)