

Panel mounting socket outlet angled - flange 100x92 fixing centers 85x77




Product description	
BALS-Prd.-Nr	1288
EAN	4024941012881
Product category	Panel mounting socket outlet, angled
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	other
Height	110mm
Width	101mm
Depth	100mm
Flange size vertical in mm	100mm
Flange size horizontal in mm	92mm
Drill hole dist. vertical mm	85mm
Drill hole dist. horizontal mm	77mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	The inclination is 20°

Logistics data	
Weight/pcs	0.288 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941012881
Length	100 mm
Width	101 mm
Height	110 mm
Weight	0.289 kg
Volume	1,111 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941967648
Length	295 mm
Width	185 mm
Height	215 mm
Weight	3.044 kg
Volume	9,975 ccm



Ampere Polzahl	16 4	16 5	32 3	32 4	32 5
a	100,0	100,0	100,0	100,0	100,0
b	92,0	92,0	92,0	92,0	92,0
c	85,0	85,0	85,0	85,0	85,0
d	77,0	77,0	77,0	77,0	77,0
Ø e	5,5	5,5	5,5	5,5	5,5
f	8,0	8,0	8,0	8,0	8,0
h	28,5	29,0	50,0	50,0	34,0
i	57,5	60,0	67,0	67,0	69,0
k	65,0	70,0	75,0	75,0	78,0
l	65,0	70,0	75,0	75,0	78,0
Leiter mm² min	1,5	1,5	2,5	2,5	2,5
Leiter mm² max	4	4	10	10	10