

Ducting & Accessories



PVC Flexible Ducting

Manufactured using PVC with wire helix. Used with single spigots and in multi-duct schemes.

6 metre lengths

Duct Dia	Stock Ref
100mm	436580
125mm	436584
150mm	436588
200mm	436592

T-Series Flexible Ducting

PVC with wire helix. For use with T-Series.

6m lengths

Size	Duct Dia	Stock Ref
Size 6	175mm	566607
Size 7	225mm	566609
Size 9	300mm	566612
Size 12	400mm	566616



Insulated Flexible Ducting

Insulated ducting should be used when duct passes through an unheated area. Minimised heat loss when used with heat recovery fans. Available in 6 diameters. An additional benefit is that thermally insulated duct offers some measure of acoustic attenuation.

Fire Rating: When assessed against the integrity criterion of BS476: Part 20; 1987, the ducting is capable of providing in excess of 25 minutes integrity from inside to outside.

10 metre lengths

Duct Dia	Stock Ref
100mm	561654
125mm	561655
150mm	561656



Duct Y Pieces

For dividing a ventilation system, providing ducting to multiple supply or extract grilles using only a single fan source.

2x Into	1x	Stock Ref
100mm	100mm	452081
100mm	150mm	452082
125mm	125mm	455211
125mm	150mm	455212
150mm	150mm	452083
150mm	200mm	452084
200mm	200mm	452085
200mm	250mm	452078
250mm	250mm	452076
250mm	300mm	452079



Acoustic Insulated Ducting

Multiple layer aluminium/polyester laminate with micro perforated flexible core to enhance acoustic performance. Core surrounded by 25mm fibreglass insulation with outer vapour barrier.

Duct Dia	Length	Stock Ref
100mm	1m	443273
125mm	1.5m	443793
150mm	1m	443274



Reducer

Duct Size	Stock Ref
R125/100	370302
R150/100	370303
R150/125	370304
R200/150	370307
R250/200	370309
R300/100	370310
R300/200	370312



Circular Extract Diffusers

Manufactured from powder coated steel. Suitable for exhausting air and can be fitted directly to the duct or in the ceiling.

Duct Size	Stock Ref
100 Ø	10544100
125 Ø	10544125
150 Ø	10544150
200 Ø	10544200



Circular Supply Diffusers

Manufactured from powder coated steel. Suitable for supplying air and can be fitted directly to the duct or in the ceiling.

Duct Size	Stock Ref
100 Ø	10543100
125 Ø	10543125
150 Ø	10543150
200 Ø	10544200