Perfect for.....

Smarter chiselling designs to solve specific trade jobs

Channelling Chisels



Ideal for:

An innovative range of channelling chisels which feature precision ground cutting edges combined with cranked shafts to rapidly produce channels for conduit installations

Typical applications include:

30mm - electrical conduit or pipe work 55mm - double conduit runs or when using capping 20mm extended - running cables

behind skirting boards or ceiling coving

Medium density block work, soft bricks, lightweight blocks, natural stone

Carbide Tipped Raking Chisels



Ideal for:

Working in the toughest masonry and concrete. The solid tungsten carbide strip insert provides the ultimate performance in material removal

Use in:

Heavy duty concrete, general concrete, hard bricks, soft bricks, lightweight block, natural stone, constructional granite, limestone, mortar

Scutch Comb Chisel



Ideal for:

Scutch Comb Holders for general masonry tasks e.g. masonry dressing, levelling uneven masonry surfaces, forming channels, back box holes etc

Use in:

General concrete, soft bricks, lightweight blocks, mortar, limestone, constructional granite, natural stone, hard bricks, heavy duty concrete

YOU KNOW?

Our SDS Plus Channelling & Scutch Comb Chisels are precision performance standards

Scan me for demo

video of Channelling Chisels









Channelling Chisels can be sharpened when the cutting edges become blunt, ideally using a grinder or good quality file and replicating the original profile as much as possible

TECH TIP!

It is necessary to try and keep all Scutch Comb teeth in contact with the material being chiselled to avoid the comb being levered out of the holder

SDS Plus Channelling & Scutch Comb Chisels

Description	Diameter Size mm	Overall Length mm	Working Length mm	Part Number	
30mm Channelling Chisel	30	225	-	G225B4CC30	
55mm Channelling Chisel	55	225	-	G225B4CC50	
20mm Extended Channelling Chisel	20	310	-	G310B4CCSB	
30mm Wide Raking Chisel - Carbide Tipped Solid-section carbide tip	30	150	-	G30B4CCCT	
55mm Wide Raking Chisel - Carbide Tipped Solid-section carbide tip	55	150	-	G55B4CCCT	
Scutch Comb Chisel - for 40mm Combs Uses SCCO combs	-	200	-	G150B4SCH	
40mm Scutch Comb Fits directly into G150B4SCH & G300MXSCH Chisels	-	n/a	-	SCCO	www.
40mm Scutch Comb - pack of 5	-	-	-	SCCOX5	
Scutch Comb Chisel - for 25mm Combs Uses SCC01 combs	n/a	200	n/a	G150B4SCH1	
25mm Scutch Comb Fits directly into G150B4SCH1	n/a	n/a	n/a	SCCO1	honey
25mm Scutch Comb - Pack of 5	n/a	n/a	n/a	SCCO1X5	Maria July



SDS Plus shanks should be greased prior to and during use. This reduces heat build-up which reduces wear on the chisel and on the machine



Each TC raking chisel is as short as possible for added power transmission to improve chiselling performance

Prior to using chisels, please ensure your machine has the 'chisel only' function as they are designed to be used on this function only









Designed for use in SDS Max machines when working in the toughest masonry and concrete See page 47