



Retrofit Surge Protection Units

- Suitable for use on TN-C-S (PME) / TN-S / & TT networks.
- Provides protection against the effects of transient over voltages.
- Ideal for installation where it is not possible to accommodate a suitable surge arrester directly within the existing consumer unit.
- Designed and tested for use with Lewden branded distribution boards.
- 5-year warranty.
- Integral coloured flag indicating SPD health status.



SRG1VCU-RM

TECHNICAL DATA		REGISTRY	
Surge protective class	Type 2	Dimensions	250x135x87mm (HWD)
Manufacturing material	Steel	Net weight	1.87KG
Type of protection	MCB	Gross Weight	1.93KG
Frequency	50-60Hz	EAN Code	5026992043110
Phase	1	Min order quantity	1
Rated operating voltage	230V		
Earthing Systems	TT	REFERENCE STANDARDS	STANDARDS
Earthing Systems	TN-C-S-(PME)	EN 61643-11:2012	
Earthing Systems	TN-S	EN 61439-2:2011	
Nm dischar. current(In)(8/20uS	40kA (N/PE)	EN 61439-1:2011	
Nm dischar. current(In)(8/20uS	20kA (L/N,L/PE)	IEC 61643-11:2011	
Voltage protection level (Up)	<1,5kV (L/PE)		
Voltage protection level (Up)	<1,5kV (L/N)		
Voltage protection level (Up)	<1,5kV (N/PE)		
For cables ø	35mm2		