



Type 2 , Single Phase, 1 Module SPDs

- Designed and tested for use with Lewden branded distribution boards
- Suitable for use in TN-C-S (PME) / TN-S / TT network systems
- Earth leakage free and may be connected before or after RCCB/RCBO circuit protection



SRGT2CU

TECHNICAL DATA		REGISTRY	
Surge protective class	Type 2	Net weight	0.11KG
Rated operating voltage	230V	Min order quantity	1
Frequency	50-60Hz	EAN Code	5026992040201
Earthing Systems	TN-S	Gross Weight	0.12KG
Earthing Systems	TN-C-S-(PME)	Dimensions	90x18x67mm (HWD)
Earthing Systems	TT		
Recommender backup MCB	40A/50A B/C 6kA MCB	REFERENCE STANDARDS	STANDARDS
Nm dischar. current(In)(8/20uS	40kA (N/PE)	IEC 61643-11:2011	
Nm dischar. current(In)(8/20uS	20kA (L/N,L/PE)	EN 61643-11:2012	
Maximum discharge current	40kA		
Voltage protection level (Up)	<1,5kV (N/PE)		
Voltage protection level (Up)	<1,5kV (L/N)		
Voltage protection level (Up)	<1,5kV (L/PE)		
Phase	1		
Modules Number	1		
Signalling contact	NO		
Execution	DIN RAIL MOUNTING		