


KINGSTON PANEL UGR<19 TRI-COLOUR 300X300 10W TP(A) DIMMABLE DALI

NET-39-03-38



Key Data

Power	10W
Luminous Flux	950lm/1080lm/1000lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP40 Front/IP20 Rear
Dimensions	295 x 295 x 10mm
Warranty	5 Years (Registration Required)

Compatible Accessories

Part Number	Description
NET-46-16-02	Universal LED Panel Suspension Kit
NET-39-16-03	Burgess Z Clips for Kingston Panels

NET LED Lighting

Buckingham Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ


T: 01223 851505 | sales@netled.co.uk | www.netled.co.uk



ORDER BY 6PM
FOR NEXT DAY DELIVERY

Technical Specifications

Input Voltage (AC)	200-240V
Power Factor	>0.95
Luminaire Efficacy	108lm/w
LED Manufacturer	JUFEI
LED Type	SMD 4014
No. of LEDs	120
Driver Manufacturer	Tridonic Excite Series
Driver Output Voltage (DC)	30-42V
Total Circuit Power (w)	10W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	95°
Dimmable	Yes
Flicker-Free	Yes
Operating Temp.	0°C to +45°C
Lifespan LM80	50,000 Hours
Diffuser Flammability Rating	TP(a)
UGR Rating	Less than 19
Diffuser/LGP Material	PC/PMMA
Weight	0.715Kg
Manufacturer	Lumlux Corp.



Other Options

Product Code	Description
NET-39-03-00	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Standard
NET-39-03-32	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Emergency
NET-39-03-34	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Self Test Emergency
NET-39-03-35	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable one4all
NET-39-03-36	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable Emergency
NET-39-03-37	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable Self Test Emergency
NET-39-03-38	Kingston Panel UGR<19 Tri-Colour 300x300 10W TP(a) Dimmable DALI Emergency

NET LED Lighting

Buckingway Business Park, 300 Anderson Road,
Swavesey, Cambridge, CB24 4UQ



ORDER BY 6PM
FOR NEXT DAY DELIVERY