

Product Specification Sheet

Polypropylene & Nylon Conduit & Glands



- -40°C to +120°C
- Self extinguishing
- High impact Strength
- Highly flexible
- Manufactured to BS EN 61386



- -20°C to +90°C
- Self extinguishing
- Acid resistant
- Manufactured to BS EN 61386

Nylon PA6 - Black

Part Number	OD	ID	Size (mm)	Length (m)	Pack Qty
KNY12/50M	14.5	10	12	50	1
KNY16/50M	15.6	11.8	16	50	1
KNY20/50M	19.7	14.8	20	50	1
KNY25/50M	24.7	19.1	25	50	1
KNY32/25M	31.7	24.8	32	25	1
KNY40/25M	41.8	35.4	40	25	1
KNY50/25M	47.9	40.4	50	25	1

Polypropylene - Black

Part Number S = Split W = White	OD	ID	Size (mm)	Length (m)	Pack Qty
KNP-S10/50M	11.8	7	10	50	1
KNP10/50M	11.8	7	10	50	1
KNP12/50M	14.2	10	12	50	1
KNP-S16/100M	15.6	11.8	16	100	1
KNP16/100M	15.6	11.8	16	100	1
KNP20/100M	19.7	14.8	20	100	1
KNP-S25/50M	24.7	19.1	25	50	1
KNPW-S25/50M	24.7	19.1	25	50	1
KNP25/50M	24.7	19.1	25	50	1
KNP32/50M	31.7	24.5	32	50	1
KNP40/25M	41.8	35.4	40	25	1
KNP50/25M	47.9	40.4	50	25	1



- -20°C to +90°C
- Hinged
- IP40

Hinged - Polypropylene

Part Number W = White G = Green	Size Nominal	Pack Qty
KNGH16/M16	16	10
KNGH16G/M16	16	10
KNGH20/M20	20	10
KNGH20G/M20	20	10
KNGH20W/M20	20	10
KNGH25/M25	25	10
KNGH25W/M25	25	10
KNGH32/M32	32	10
KNGH40/M40	40	10
KNGH50/M50	50	10



- -40°C to +120°C
- One piece
- IP66

Male Gland - Nylon

Part Number	Size Nominal	Pack Qty
KNYG12/M16	12	10
KNYG16/M16	16	10
KNYG20/M20	20	10
KNYG25/M25	25	10
KNYG32/M32	32	10
KNYG40/M40	40	10
KNYG50/M50	50	10



- -40°C to +120°C
- One piece
- IP66

Male 90° Gland - Nylon

Part Number	Size Nominal	Pack Qty
KNYGE16/M16	16	10
KNYGE20/M20	20	10
KNYGE25/M25	25	10
KNYGE32/M32	32	10
KNYGE40/M40	40	10
KNYGE50/M50	50	10