

Product Specification Sheet

Galvanised Steel Conduit & Glands



- -100°C to +300°C
- High mechanical Strength
- Highly flexible
- IP40
- Manufactured to BS EN 61386



- -15°C to +70°C
- High mechanical Strength
- Highly flexible
- IP54
- Manufactured to BS EN 61386

Galvanised Steel - Self Coloured

Part Number	OD	ID	Size (mm)	Length (m)	Pack Qty
KMS16/**M	16.4	12.9	16	10, 30, 50	1
KMS20/**M	20.3	16.8	20	10, 30, 50	1
KMS25/**M	24.3	20.9	25	10, 30, 50	1
KMS32/**M	32.7	29.0	32	10, 30	1
KMS40/10M	41.8	35.4	40	10	1
KMS50/10M	47.9	40.4	50	10	1
KMS63/10M	59.7	51.6	63	10	1
KMS75/10M	77	70.0	75	10	1

** add reel length eg: KMS25/10M

PVC Coated Galvanised Steel - Black

Part Number	OD	ID	Size (mm)	Length (m)	Pack Qty
KMPS12/50M	14.2	10	12	50	1
KMPS16/**M	17.4	12.9	16	10, 30, 50	1
KMPS20/**M	21.4	16.8	20	10, 30, 50	1
KMPS25/**M	25.7	20.9	25	10, 30, 50	1
KMPS32/**M	33.9	29.0	32	10, 30, 50	1
KMPS40/**M	41.8	35.4	40	10, 30	1
KMPS50/10M	47.9	40.4	50	10	1

** add reel length eg: KMPS20/50M



- -100°C to +300°C
- High mechanical Strength
- 2 part fitting

Male Fixed Gland - Nickel Plated Brass

Part Number	Size Nominal	Pack Qty
KMG12/M16/F	12	10
KMG16/M16/F	16	10
KMG16/M20/F	16	10
KMG20/M20/F	20	10
KMG25/M25/F	25	10
KMG32/M32/F	32	2
KMG40/M40/F	40	2
KMG50/M50/F	50	2
KMG63/M50/F	63	2
KMG75/M75/F	75	2



- -100°C to +300°C
- High mechanical Strength
- 2 part fitting

Male Swivel Gland - Nickel Plated Brass

Part Number	Size Nominal	Pack Qty
KMG16/M20/S	16	10
KMG20/M20/S	20	10
KMG25/M25/S	25	10
KMG32/M32/S	32	2