

STEEL

- PVC coating - Black

IP54

FSU-CP20B M20 thread



- 10 metres of galvanised steel with PVC coating
- Temperature range -15°C to +70°C
- Self extinguishing
- High mechanical strength
- Highly flexible
- 5 M20 fixed fittings
- 5 M20 swivel fittings
- 10 steel locknuts
- IP54

NYLON

- Black



IP66

FPAS-CP21B M20 thread

FPAS-CP25B M25 thread



- 10 metres of standard weight nylon PA6 FPAS21 or FPAS25
- Low fire hazard
- Halogen free
- Self extinguishing
- Low smoke and Low toxicity
- High flexibility and fatigue life
- High impact strength
- Oil and solvent resistant
- UV resistant
- Temperature range -40°C to +120°C
- 10 FPA fittings and locknuts FPA21-M20B or FPA25-M25B
- One part, fast fit
- Removable using a screwdriver
- High pull-off strength
- Anti-vibration
- IP66
- UV resistant

PVC SPIRAL

- Black

IP65

FPC-CP20B M20 thread

FPC-CP25B M25 thread



- 10 metres of spiral reinforced pvc FPC20 or FPC25
- Highly flexible
- Accepts torsional movement
- Self extinguishing
- UV resistant
- Temperature range -5°C to +70°C
- 10 MPC fittings and locknuts
- IP65
- UV resistant
- Smooth bore

NYLON

- Black

IP66

FPYE-CP20B M20 thread

FPYE-CP25B M25 thread



- 10 metres of light weight nylon PA6 FPAL20 or FPAL25
- Flexible
- Halogen free
- Self extinguishing
- Temperature range -40°C to +120°C
- 10 Flexilok fittings and locknuts FLK20-M20B or FLK25-M25B
- IP66
- One part, fast fit

POLYPROPYLENE

- Black or Grey

IP66

FPP-CP20B M20 thread

FPP-CP25B M25 thread

FPP-CP34B M32 thread



- 10 metres of polypropylene FPP20, FPP25 or FPP34
- Temperature range -20°C to +90°C
- Self extinguishing
- To specify grey change B to a G eg: FPP-CP20G
- 10 Flexilok (PP) fittings and locknuts FLK20-M20BPP, FLK25-M25BPP or FLK34-M32BPP
- IP66
- One part, fast fit

Standards



Don't forget

See page 125

