

## White Products

**Construction:** Polypropylene or upvc conduit system with nylon straight, 90° elbow, coupler and conduit clips options.

### Conduit

FPP
For details see page 45
IP66

  

FPL
For details see page 66
IP66

### Fittings

FLK	FLK-90	FLK-FLK	FCL	FCL-P
<b>Straight external thread</b> One piece, slim, fast fit, external threaded fitting suitable for knockouts or threaded entries.	<b>90° Elbow external thread</b> One piece, slim, fast fit, external threaded 90 degree elbow fitting suitable for knockouts.	<b>Coupler</b> One piece, fast fit, slim coupler to join corrugated conduits.	<b>Nylon corrugated conduit clip with integral lid</b> Nylon PA66 conduit clip with integral lid for increased security. Incorporates internal ribs to prevent conduit from pulling through.	<b>Nylon plain conduit clip with integral lid</b> Nylon PA66 conduit clip with integral lid for increased security and plain internal diameter for use with rigid conduit or smoothbore flexible conduit.
IP66	IP66	IP66		



European (NW) sizes	OD mm	FPP	FPL
20	20.0	FPP20W-50M	FPL20W-100M
25	25.0	FPP25W-50M	FPL25W-50M
34	34.5	FPP34W-50M	FLK34-M32W

Ext Metric	Ext Metric			
FLK20-M20W	FLK20-M20-90W	FLK20-FLK20W	FCL20W	FCL20W-P
FLK25-M25W	FLK25-M25-90W	FLK25-FLK25W	FCL25W	FCL25W-P
FLK32-M32W*				

### PVC - Contractor pack white

FPL-CP20W	M20 thread
FPL-CP25W	M25 thread



- 10m of FPL white conduit
- 10 x Flexilok® fittings
- 10 x Locknuts

### LPC

**Smooth bore, smooth cover, helically formed pvc, flexible conduit with spiral upvc reinforcement and flexible pvc jacket.**

IP66 IP67 IP68

Available in 20mm and 25mm sizes. Use with FCL-P clips to secure.

See page 76 for more details

### MPC

**Straight nylon compression fitting with external thread**

IP66 IP67 IP68

2 part compression fitting with internal spigot and all round teeth to grip conduit.

See page 77 for more details

### Standards

