

SLB2300

2300W PIR Light Controller – Black

Features & Benefits

- Pan and tilt feature
- Light ON times adjustable
- LUX (light level) adjustment – Day to Night
- Manual ON/OFF switching override
- IP55 weatherproof rating
- Simple and quick to fit terminal block connectors
- Corner mounting bracket available – SLBCB (Sold Separately)



Technical Data

| | |
|------------------------------|---|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Surface |
| Earth Class Rating | Class I |
| Operating Temperature | -20°C to 40°C |
| Ingress Protection Rating | IP55 |
| Setting Type | Dial |
| Approved Mounting Height (m) | 2.5 |
| Motion Detection (m) | 12 |
| Detection Angle | 180° |
| Pan & Tilt Adjustment | 90° Left/Right From Centre, Tilt 15° (Up), 60° (Down) |
| Mounting Hole Centres (mm) | 50 |
| Standby Consumption | <1W |

Data sheet

SLB2300

Light / PIR Lighting Controllers

| | |
|-----------------------|---|
| Number of Channels | 1 |
| Switch rating | 250W LED, 500W Fluorescent, 2300W Halogen |
| ON Time Adjustment | 5 Seconds to 15 Minutes. User Adjustable |
| Lux Level | 5 to 1000 |
| Detection Range (M) | 12 |
| Permanent ON Facility | Yes (Pulse Override) |
| Dusk Till Dawn | No |
| Multiple Unit Support | Up to 4 Units In Parallel |
| Cable Entry(s) | Back Entry, Bottom Entry |

General

| | |
|-----------------------------|-------------------------------|
| Weight (g) | 193 |
| Height (mm) | 95 |
| Width (mm) | 78 |
| Depth (mm) | 141 |
| Body Construction | Polycarbonate |
| Product Colour | Black |
| Accessories (Included) | Fittings (Rawl Plugs, Screws) |
| EAN Number | 5012483013205 |
| Guarantee Period | 3 Years |
| Trade Tariff Commodity Code | 8536508090 |

Line Diagrams

