

SLW360N

PIR Presence Detector

Features & Benefits

- Slimline sensor head design
- 360° detection zone for optimum coverage
- IP44 weatherproof rating (internal use only)
- Manual override (Pulse) for extended light on times
- Adjustable time setting
- Adjustable LUX setting
- Besa Box Mountable



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Approved Mounting Height (m)	2.5
Presence Detection (m)	4 Diameter
Motion Detection (m)	8 Diameter
Detection Angle	360°
Mounting Hole Centres (mm)	84
Standby Consumption	<0.5W
Number of Channels	1

Data sheet

SLW360N

Light / PIR Presence Detectors

Switch rating	500W LED (PF>0.9), 2000W Halogen, 500W Fluorescent, 75W Fan
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
Lux Level	1 to 1000
Detection Range (M)	8 Diameter
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 8 Units In Parallel
Cable Entry(s)	Back Entry, Side On Knockouts

General

Weight (g)	106
Height (mm)	105
Width (mm)	105
Depth (mm)	45
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings, Backplate
EAN Number	5012483014783
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

