Accessories

Around the House

PIR Sensor

- Sensor to detect motion in correlation with daylight level
- Including remote control to adapt sensor settings
- Earth spike included, suitable for wall-mounting
- Reliable on/off function thanks to infrared technology
- IP65
- Ambient temperature: -20 to +40 °C
- Switching load: 800W
- Electrical class: I
- Connection via THORNeco cable system or adaptor with open leads (included)



- Cable diameter 6.5 - 12 mm

Conny IP68 Connector


- Quick connector 3 pole

- Suitable for outside and

inground use

- Tool free

- Rated cross-section rigid, single and fine stranded 1-2.5 mm²



Description	Cat. No.
CONNY IP68 QUICK CONNECTOR 16A 3-POL	CONIPCON





Detection range

① Time	10 s, 90 s, 5 min, 10 min, 15 min, 20 min, 30 min	
₩ lux	10 lux, 50 lux, 100 lux, 200 lux,	

Description	Cat. No.
ECO PIR SENSOR	ECOPIR


Controllability

Photocell

- Detection of daylight/brightness level
- Switch to determine on which brightness level lights should turn on
- Earth spike included, suitable for wall-mounting
- IP65
- IK04
- Ambient temperature: -20 to +40°C
- Switching load: 200W
- Electrical class: I
- Connection via THORNeco cable system



Cat. No.
ECOPCELL









Description ECO PC SENSOR

or adaptor with open leads (included)





Cables & Connectors

- Tool free
- 3 pole
- IP68
- High mechanical strength
- Flexible cable H07RN-F 3G 1.5 mm²
- Cable suitable for outside and inground use*





Mains adaptor: connects luminaires of the THORNeco cable system to mains (one side: Conny connector, other side: Female)

External integrator: connects luminaires of other suppliers to the THORNeco cable system (one side: Male, other side: Conny connector)

Ordering guide

Description	Cat. No.
ECO EXTENSION CABLE 1M	ECOEXTC1M
ECO EXTENSION CABLE 2M	ECOEXTC2M
ECO EXTENSION CABLE 5M	ECOEXTC5M
ECO EXTENSION CABLE 10M	ECOEXTC10M
ECO MAINS ADAPTOR	ECOMAINSAD
ECO EXT INTEGRATOR	ECOEXTINT
ECO T-CONNECTOR	ECOTCON
ECO MULTICONNECTOR	ECOMULTICON

^{*}The suitability might differ according to different national regulations





Extension cable with Male/ Female connector in different lengths (1 m, 2 m, 5 m, 10 m)

T-Connector for extension (1 Male, 2 Female)



Multiconnector for extension (1 Male, 6 Female including protection caps)