



## MYHEAT Underfloor Heating Mats

Underfloor Heating Mats are a combination of a heating cable attached to a fibreglass mesh scrim that makes installation easy. The mat can simply be rolled out onto the floor saving precious time. The mats have double sided tape on the underside so they can easily be fixed to any clean surface.

[Get a Quote](#)

### Further Information

The ultra thin radiant heating mats, rated 150W/m<sup>2</sup> and 200W/m<sup>2</sup>, can easily be fitted directly onto your existing tiled floor without needing to remove it. The mats can be installed within the thickness of the tile adhesives and therefore adds no significant height to the floor level. Consequently, there should be no requirement to reduce door heights or raise skirting boards.

- 150W/m<sup>2</sup> mats are suitable as a primary heating source in well insulated dwellings with a large surface area.
- 200W/m<sup>2</sup> mats are suitable as a primary heating source in not so well insulated dwellings with a smaller surface area. They are ideal for conservatories, large hallways and lobbies - anywhere that you need more heat

MYHEAT radiant floor heating mats feature a twin conductor design with a single 3 metre long 'cold tail' connections lead (only one connection cable to the thermostat).

The mats are supplied together with a 2mtr length of 12mm flexible conduit for the floor sensor (supplied with the thermostat).

## Product Codes

| 150W/m <sup>2</sup> |                                     |            |            |
|---------------------|-------------------------------------|------------|------------|
| Part Code           | Area to be heated (m <sup>2</sup> ) | Output (W) | Length (m) |
| 15OMH0.5            | 0.5                                 | 75         | 1.0        |
| 15OMH1.0            | 1.0                                 | 150        | 2.0        |
| 15OMH1.5            | 1.5                                 | 225        | 3.0        |
| 15OMH2.0            | 2.0                                 | 300        | 4.0        |
| 15OMH2.5            | 2.5                                 | 375        | 5.0        |
| 15OMH3.0            | 3.0                                 | 450        | 6.0        |
| 15OMH3.5            | 3.5                                 | 525        | 7.0        |
| 15OMH4.0            | 4.0                                 | 600        | 8.0        |
| 15OMH4.5            | 4.5                                 | 675        | 9.0        |
| 15OMH5.0            | 5.0                                 | 750        | 10.0       |
| 15OMH6.0            | 6.0                                 | 900        | 12.0       |
| 15OMH7.0            | 7.0                                 | 1050       | 14.0       |
| 15OMH8.0            | 8.0                                 | 1200       | 16.0       |
| 15OMH9.0            | 9.0                                 | 1350       | 18.0       |
| 15OMH10.0           | 10.0                                | 1500       | 20.0       |
| 15OMH11.0           | 11.0                                | 1650       | 22.0       |
| 15OMH12.0           | 12.0                                | 1800       | 24.0       |
| 15OMH14.0           | 14.0                                | 2100       | 28.0       |
| 15OMH16.0           | 16.0                                | 2400       | 32.0       |

| 200W/m <sup>2</sup> |                                     |            |            |
|---------------------|-------------------------------------|------------|------------|
| Part Code           | Area to be heated (m <sup>2</sup> ) | Output (W) | Length (m) |
| 200MH1.0            | 1.0                                 | 200        | 2.0        |
| 200MH1.5            | 1.5                                 | 300        | 3.0        |
| 200MH2.0            | 2.0                                 | 400        | 4.0        |
| 200MH2.5            | 2.5                                 | 500        | 5.0        |
| 200MH3.0            | 3.0                                 | 600        | 6.0        |
| 200MH3.5            | 3.5                                 | 700        | 7.0        |
| 200MH4.0            | 4.0                                 | 800        | 8.0        |
| 200MH4.5            | 4.5                                 | 900        | 9.0        |
| 200MH5.0            | 5.0                                 | 1000       | 10.0       |