

Product Data Sheet



NETATMO PRO NETATMO

Netatmo Pro Additional Smart Radiator Valve

REF. NAV-PRO | EAN. 3700730502689

> Link to e-catalog product sheet

Technical characteristics

Adjustment element	Other
Temperature sensor model	Other
Medium	Air
Suitable for immersion tube	Yes
Connection size insert probe	Other
Suitable for radiator	Yes
With anti-theft security	No
Suitable for anti-theft protection	No
Blocking/limiting adjustment range	Yes
Mechanically lockable at zero (off) position	No
Response time	1 s
Suitable for heating	Yes
Suitable for cooling	No
Suitable for tap water	Yes
Frost protected	No
Remote operation	Yes
Max. length of cable/capillary tube to remote control element	0 m
Length of cable/capillary tube to remote sensor	0 m
Diameter remote sensor	0 mm

Overall depth/length	80 mm
Degree of impact strength (IK)	Not applicable
Degree of protection (IP)	IP30
Operating / setting temperature	0-50 °C
Storage temperature	0-50 °C
Type of voltage	AC/DC
Supply voltage	2.5-3 V
Supply current	0.00001-0.6 A
Standby consumption	0.01 mA
Colour	White
Halogen-free	Yes
Contains Batteries and/or Accumulator	Yes
Addressable	No
Connected object	Yes
Communication type	RF
Application store for download	Google Play Store
Programming way	Smartphone apps
With voice command	Yes
Programmable	No
Interoperable connection Protocol	No



Length remote sensor	0 mm
Operation by Bluetooth	No
Operation by app	Yes
With web interface	Yes
Overall width	58 mm
Overall height	58 mm

Connectable by Internet box	No
Compatible voice assistants	Amazon Alexa
Application name	Home + Control
Product use function	Thermal comfort management

Documents

Technical documentation

QSG2-NAV-V2-WEB.pdf | PDF (0.65Mo)

Agreements & certificates

■ LGRP-01537-V01.01-EN.pdf | PDF (0.65Mo)