

DCG200T2-GB

54V XR FLEXVOLT Wall Chaser - 2 X 6Ah

The world's first cordless wall chaser, powered by 54V XR FLEXVOLT batteries and a brushless motor to deliver a maximum cutting depth of 32mm into solid concrete with an adjustable cutting width from 8 to 35mm. Other features include Wireless Tool Control to enable automatic stop start dust extraction when used with the DCV586M, tool free cutting depth adjustment with park position and an electronic clutch to protect the user from kick back.With 2 X 6Ah batteries, charger and TSTAK kitbox.

Selling Propositions

- 54V XR FLEXVOLT battery provides maximum power and performance
- Tool free quick release guard for easy blade access
- Wireless Tool Control transmitter which allows the tool to be wirelessly paired with another Wireless Tool Control device, such as a dust extractor, for automatic activation and shut down
- Tool Connect Tag securing location allowing inventory management and tracking via the Tool Connect app. DCE041 Tool Connect Tag sold separately
- Tool free blade height adjustability with Park position
- 54V Brushless motor enables improved performance in demanding applications
- Electronic Brake stops the wheel quickly when the trigger is disengaged
- Electronic Clutch reduces the kickback reaction in the event of a pinch or stall
- A mesh cover over air intake vents restricts dust being sucked through the motor
- Rubber overmould provides enhanced grip and comfort
- Built in dust extraction port allowing direct connection to dust extractor, or DEWALT AirLock system

Standard Equipment

- Premium diamond blades (2)
- 3mm, 6mm, 9mm & 12mm spacers (1)
- Chisel (1)
- Hex blade wrench (1)
- Deep TSTAK kit box (1)
- 9.0Ah XR FLEXVOLT battery packs with state of charge indicator (2)
- Multi-voltage charger (1)

Warranty specifications

- Dewalt European Warranty 3 years (subject to registration)

Specifications	
Blade Bore	22.23 mm
No Load Speed	9000 rpm
Depth of cut	32.0 mm
Blade Diameter	125.0 mm
Weight	3.7 kg
Power Source	Cordless
Product Type	Handheld
Battery Capacity	6.0 Ah
Battery Chemistry	XR FLEXVOLT
Dust Solution Compatible	Yes
Weight (incl. battery)	4.8 kg
Uncertainty K 1 (Vibration)	1.5 m/s²
Sound Pressure	102.0 dB(A)
Sound Pressure Uncertainty	3.0 dB(A)
Sound Power	113.0 dB(A)
Sound Power Uncertainty	3.0 dB(A)
Hand/Arm Vibration	4.7 m/s²
Spindle diameter	14.0 mm
Blade Thickness	3.0 mm
Width of cut	35.0 mm