

ARCA 403021

FIBOX
Enclosing innovations



Sample image

Order symbol : ARCA 403021

Product nr : 8120007

UL Code : UL508A

Description : Cabinet, PC


Remarks : Grey cover, 2-point locking, hinges on the long side

EAN : 6418074079183

El. number :

- Finland : 3423054
- Denmark : 8212091058
- Sweden : 2500114

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions :

mm :

Height

400

Width

300

Depth

210

Accessories :

DRS ARCA

DIN rail frame set

inch :	11.81	15.75	8.27
Materials :			
Material :	Polycarbonate		
Base colour :	RAL_7035		
Cover colour :	RAL 7035 -light grey		
Gasket material :	Polyurethane		
Temperatures :			
Temperature °C (continuous) :	-40 ... 80		
Temperature °F (continuous) :	-40 ... 175		

403021	(385 x 285 x 35)
RCS ARCA 4030	Rain canopy set for size 4030
IDS ARCA 4030	Inner door set (385 x 285 x 35)
PMK ARCA 30	PoleMounting kit, for pole ø100-300mm (385 x 285 x 35)
DSP ARCA VLS	Door stopper ARCA, vertical, left, small
MPMP ARCA 4030	Mounting plate multiperforated (350x250x2 mm - ø3.6 mm)
DSP ARCA VRS	Door stopper ARCA, vertical, right, small
MPS ARCA 4030	Mounting plate (350x250x2 mm) (350 x 250 x 2)
MPP ARCA 4030	Mounting plate perforated (350x250x2 mm - 26x11 mm) (350 x 250 x 2)
MPX ARCA 4030	Mounting plate (350x250 mm) (350 x 250 x 15)

Ratings :	
Ingress protection (EN 60529):	IP66;
Impact Resistance (EN 62262):	IK10;
electrical_insulation :	Totally insulated
Halogen free (DIN/VDE 0472, Part 815) :	Yes
UV resistance :	UL 746C
Flammability Rating :	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C :	960C
NEMA Class	NEMA__1_4_4X_12_13

Certificates :	
Certificate FI 40467	