



50,000
HOURS



YEARS'
WARRANTY



NEXT DAY
DELIVERY



VENTURE
LIGHTING

From our
Industrial Range



Our new **slim Lobay** has the **LED chambers mounted separately** to aid in thermal management and LED performance. This **boosted performance** results in **remarkable rated life benefits**. Achieving **90% lumen maintenance** at the **rated life of 50,000 hours**.

LOBAY



Order Code: IND240

Photometric Data	
Lumens	14500
Colour Rendering Index (CRI)	80-89
LPW (lm/W)	140
Colour Temperature (K)	4000 - 4000
SDCM	5
Beam Angle (°)	120
Light Distribution	Symmetric
Lens / Reflector	Diffuser lens/optic/panel

Life Data	
Rated Life @ 25°C (Hrs)	50000
Rated Life @ Tmax (Hrs)	50000
Rated Life L80/B50 @ Tmax (Hrs)	50000

Electrical Data	
Thermal Overload Protection	Yes
Overvoltage Protection	Yes
Input (W)	100
Input (V)±10%	100 - 240
Voltage Type	AC
Input Current (A)	0.5
Power Factor	0.95
No. Per C16 Breaker	10
Energy Efficiency Class (EEC)	A++, A+, A (LED)
Electrical Class	I
Type of Wiring	Ending
Wiring X-sec (mm^2)	1.5
Non-dimmable	Yes
LED Nominal Current (mA)	2200 - 2200
Emergency Lighting	Yes
Short Circuit Protection	Yes

Physical Data	
With Protective Cover	Yes
Degree of Protection (IP)	IP20
Mounting Method	Pendant
Housing Colour	White
Housing Material	Steel
Reflector	White
Length (mm)	630
Width (mm)	325
Height/Depth (mm)	53
Weight (kg)	3.1
Lamp Type	LED Not Exchangeable
Warranty (year)	5



Order Code: IND240

Environmental Data

Ambient Rated Temperature Range (°C)	-20 to 40
--------------------------------------	-----------

Accessories

ACS153 - Programming Remote for SB Sensor

ACS214 - Trunking Mount Bracket Kit

Logistical Data

Item Gross Weight (kg)	4.2
------------------------	-----

Packaging Length (cm)	86
-----------------------	----

Packaging Width (cm)	36
----------------------	----

Packaging Height (cm)	13
-----------------------	----

Carton Quantity	1
-----------------	---