

**ACCENTPLUS SCOOP ADJUSTABLE DOWNLIGHT 30W 3500LM 115LM/W
4000K CRI90 185MM CUTOUT 36 BEAM WHITE 220-240V - NON-DIMM**

ILD185SC012



Integral Scoop downlights are a commercial solution for washing walls or displays with high quality CRI 90 real colour lighting. They feature fully rotatable bezels and a 38° downward tilt which brings the fitting well below the ceiling line allowing precise beam control, lighting areas that would not be possible with conventional downlights. The range includes versions with no driver, which can be paired to our standard DALI, push dim, 0-10V combination dimmable drivers (see suggested products for driver options).

Details

Quick Order Code:	283685
Barcode:	5055788276562
Category:	Downlights
Range Name:	AccentPlus Scoop
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Features:	Adjustable
Fixed/Tiltable:	Tiltable
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Depth (mm):	145
Product Weight (g):	1290
Overall diameter (mm):	200
Construction:	Aluminium
Cut Out Diameter (mm):	185
Bulb or Luminaire Shape:	Round
Luminaire Fixing:	Recess mounted
Placement / Application:	Indoor, General Lighting
Spot Type:	COB

Electrical Data

Power Consumption (W) :	30
Power Factor:	0.95
Amperage (mA):	800

Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	3500
Luminous efficacy (lm/W):	115
Colour Temperature:	4000K - Cool White
Beam Angle:	36
Colour Rendering Index (CRI):	90
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
Integrated Light Source:	Yes
Lifetime (hours):	50000
Switching Cycles:	100000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	1400
Package Length (mm):	220
Package Width (mm):	220
Package Depth (mm):	170
Qty per euro pallet:	160