



# LEDEP10

Emergency converter, Self-test, maintained

## Features

|           |      |
|-----------|------|
| IP rating | IP20 |
|-----------|------|

## Installation information

|                             |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| Install Connector Type      | Mains: Push-fit terminals 0.5 - 2.5mm² DC: Plug & Play connectors |
| Insulation Coverable        | No                                                                |
| Double Insulation           | Yes                                                               |
| Cut Out Size                | Ø18mm (status LED)<br>Ø7mm (test button)                          |
| Inrush Current              | 10A                                                               |
| Construction Material       | Polycarbonate                                                     |
| Weight                      | 390g                                                              |
| Maximum Ambient Temperature | +5°C to +35°C                                                     |
| SELV                        | Yes                                                               |
| Electric Class (1, 2, 3)    | 2                                                                 |

## Wiring information

|                         |                        |
|-------------------------|------------------------|
| Cable / Flying Lead     | Plug & Play connectors |
| Type of Wiring Required | Parallel               |

## Accessories

|     |                             |
|-----|-----------------------------|
| N/A | No accessories are required |
|-----|-----------------------------|

## PRODUCT CODES

|         | Finish     | Description                                | Characteristic 1 | Characteristic 2 |
|---------|------------|--------------------------------------------|------------------|------------------|
| LEDEP10 | Matt white | Emergency converter, Self-test, Maintained | LiFePO4 battery  | 6.4V 1500mAh     |



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

5 year extended guarantee

## Features & benefits

- Self-test device, simplifying the inspections
- LiFePO4, provides long operational life
- A minimum of 3 hours of emergency lighting
- Built-in protection: - open circuit - over charging - over discharging - over temperature
- Dual colour Green / Red LED status indicator
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Synchronizes an automatic battery duration test every 6 months
- Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless

