




MASTER Glass LED bulbs

MAS LEDBulb DT7.2-75W B22 927A60CL G

Featuring a classic heritage design, these filament MASTER glass bulbs combine the familiar shapes of incandescent glass LED bulbs with the benefits of long-lasting LED technology. Ideal for creating a cosy atmosphere for customers, these glass LED bulbs provide excellent quality of light. MASTER glass bulbs can be dimmed for different lumen levels and colour temperatures (dimmable glass led bulbs). They also deliver significant energy savings, using 30% less energy compared to normal LED bulbs. By offering a lifetime of 25,000 hours, these dimmable glass LED bulbs also reduce maintenance costs.

Product data

General Information	
Cap base	B22 [B22]
Nominal lifetime	25,000 h
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
EU RoHS compliant	Yes

Light Technical	
Colour Code	922-927 [CCT of 2200K-2700K]
Luminous Flux	1,055 lm
Colour designation	Warm Glow (WG)
Correlated Colour Temperature	2200 2700 K
Luminous efficacy (rated) (nom.)	146 lm/W
Colour consistency	<6
Colour rendering index (CRI)	90
LLMF at end of nominal lifetime (nom.)	70 %

Flickering value (PstLM)	0.9
Stroboscopic effect	0.4
Photobiological safety according to EN 62471 RGO	

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	7.2 W
Lamp current (nom.)	49 mA
Wattage equivalent	75 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (nom.)	220-240 V


Temperature	
Ambient temperature range	-20°C to 45°C

MASTER Glass LED bulbs

T-Case maximum (nom.)	70 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Lamp Finish	Clear
Bulb material	Glass
Bulb shape	A60 [A 60 mm]
Approval and Application	
Energy Efficiency Class	D
Energy consumption kWh/1,000 hours	8 kWh
EPREL registration number	1189708
EyeComfort	Yes


Product Data	
Full EOC	871951446103100
Order product name	MAS LEDBulb DT7.2-75W B22 927A60CL G
Order code	46103100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material no. (12 NC)	929003011282
Full product name	MAS LEDBulb DT7.2-75W B22 927A60CL G
EAN/UPC – Case	8719514461048
EAN/UPC – Product/Case	8719514461031

Dimensional drawing




Product	D	C
MAS LEDBulb DT7.2-75W B22 927A60CL G	60 mm	103 mm

Photometric data




Spectral Power Distribution Colour - MAS LEDBulb DT7.2-75W B22 927A60CL G



General uniform lighting - MAS LEDBulb DT7.2-75W B22 927A60CL G


MASTER Glass LED bulbs

Photometric data




Light Distribution Diagram - MAS LEDBulb DT7.2-75W B22 927A60CL G

Lifetime



Life Expectancy Diagram - MAS LEDBulb DT7.2-75W B22 927A60CL G



Lumen Maintenance Diagram - MAS LEDBulb DT7.2-75W B22 927A60CL G

